

## **APPARATUS AND METHOD FOR DRIVING PLASMA DISPLAY PANEL**

### **CROSS REFERENCE TO RELATED APPLICATIONS**

This application claims priority to and the benefit of Korean Patent Application No. 2002-39713 filed on July 9, 2002 in the Korean Intellectual Property Office, the content of which is incorporated herein by reference.

### **BACKGROUND OF THE INVENTION**

#### **(a) Field of the Invention**

The present invention relates to an apparatus and method for driving a plasma display panel (PDP).

#### **(b) Description of the Related Art**

In recent years, flat panel displays such as liquid crystal displays (LCD), field emission displays (FED), PDPs, and the like have been actively developed. The PDP is advantageous over other flat panel displays in regard to its high luminance, high luminous efficiency, and wide view angle, and accordingly, it is favorable for making a large-scale screen of more than 40 inches as a substitute for the conventional cathode ray tube (CRT).

The PDP is a flat panel display that uses plasma generated by gas discharge to display characters or images, and it includes, according to its size, more than several scores to millions of pixels arranged in a matrix pattern. Such a PDP is classified as a direct current (DC) type and an alternating current (AC) type according to its discharge cell structure and the waveform of the driving voltage applied thereto.

The DC PDP has electrodes exposed to a discharge space, allowing DC to flow through the discharge space while voltage is applied, and hence it requires resistors for limiting the current. Contrarily, the AC PDP has electrodes covered with a dielectric layer that naturally forms a capacitance component that limits the current and protects the electrodes from the impact of ions during a discharge. Thus the AC PDP is superior to the DC PDP in regard to long lifetime.

Typically, the driving method of an AC PDP is sequentially composed of a reset step, an addressing step, a sustain discharge step, and an erase step.

In the reset step, the state of each cell is initialized in order to readily perform an addressing operation on the cell. In the addressing step, wall charges are accumulated on selected "on"-state cells and other "on"-state cells (i.e., addressed cells) for selecting "off"-state cells on the panel. In the sustain discharge step, a sustain pulse is applied alternately to scan electrodes (hereinafter referred to as "Y electrodes") and sustain electrodes (hereinafter referred to as "X electrodes") to perform a discharge for displaying an image on addressed cells.

In the AC PDP, the Y and X electrodes for such a sustain discharge act as a capacitive load, and a capacitance exists for the Y and X electrodes (hereinafter referred to as "panel capacitor  $C_p$ ").

Now, a description will be given as to a driver circuit for a conventional AC type PDP and its driving method.

Figs. 1 and 2 are illustrations showing a conventional driver circuit and its operating waveform.

The driver circuit generating a sustain pulse as suggested by Kishi et al. (Japanese Patent No. 3,201,603) comprises, as shown in Fig. 1, Y electrode driver 11, X electrode driver 12, Y electrode power supplier 13, and X electrode power supplier 14. X electrode driver 12 and X electrode power supplier 14 are the same in construction as Y electrode driver 11 and Y electrode power supplier 13, and will not be described in detail in the following description.

Y electrode power supplier 13 comprises capacitor  $C_1$ , and three switches SW1, SW2, and SW3. Y electrode driver 11 comprises two switches SW4 and SW5. Switches SW1 and SW2 in the Y electrode power supplier 13 are coupled in series between power source V1 and ground terminal 0. Power source V1 supplies a voltage  $V_s/2$ , and the voltage  $V_s$  is sustain discharge voltage. One terminal of capacitor  $C_1$  is coupled to the contact of switches SW1 and SW2, and switch SW3 is coupled between the other terminal of capacitor  $C_1$  and ground terminal 0.

Switches SW4 and SW5 of Y electrode driver 11 are coupled in series to both terminals of capacitor C1 of Y electrode power supplier 13. The contact of switches SW4 and SW5 is coupled to panel capacitor Cp.

As shown in Fig. 2, when switches SW1, SW3, and SW4 are turned on, with switches SW2 and SW5 off, Y electrode voltage Vy is increased to Vs/2 and capacitor C1 is charged with the voltage Vs/2. Subsequently, when switches SW1, SW3, and SW4 are turned off and switches SW2 and SW5 are turned on, the Y electrode voltage Vy is decreased to -Vs/2 by the voltage Vs/2 charged in capacitor C1.

Through this driving operation, positive voltage +Vs/2 and negative voltage -Vs/2 can be alternately applied to the Y electrodes. Likewise, positive voltage +Vs/2 and negative voltage -Vs/2 can be alternately applied to the X electrodes. The voltages  $\pm V_s/2$  respectively applied to the X and Y electrodes have an inverted phase with respect to each other. By generating a sustain pulse swinging between -Vs/2 and +Vs/2, the potential difference between X and Y electrodes can be maintained at the sustain discharge voltage Vs.

Such a driver circuit can employ elements of a low withstand voltage, because the withstand voltage of each element in the circuit is Vs/2. However this driver circuit is applicable only to plasma display panels using a pulse swinging between -Vs/2 and +Vs/2.

In addition, the capacitor for storing the voltage used as a negative voltage in this circuit must have a large capacity, so that a considerable amount of an inrush current flows in an initial starting step due to the capacitor.

### **SUMMARY OF THE INVENTION**

In accordance with the present invention, a PDP driving circuit for using switches having the low withstand voltage is provided. The present invention applies a voltage to a contact of serially coupled switches, the voltage clamping the voltage of both terminals of the switches

In one aspect of the present invention, an apparatus for driving a PDP is provided, the PDP having a panel capacitor. In the apparatus, first and second switches are coupled in series between a first power source for supplying a first voltage and a first terminal of the panel capacitor, and third and fourth switches are coupled in series between the first

terminal of the panel capacitor and a second power source for supplying a second voltage. A first capacitor is coupled between a contact of the first and second switches and a contact of the third and fourth switches. A fifth switch is coupled between the first capacitor and a third power source supplying a third voltage.

Preferably, the fifth switch is turned on so that the first capacitor is charged to the difference between the first and third voltages, and the third voltage is substantially a middle voltage between the first and second voltages.

The apparatus further includes at least one inductor coupled to the first terminal of the panel capacitor; and sixth and seventh switches coupled in parallel between the inductor and the third power source.

It is preferable that the first to fourth switches have a body diode.

The apparatus may further include: sixth and seventh switches coupled in series between the first power source and a second terminal of the panel capacitor; eighth and ninth switches coupled in series between the second terminal of the panel capacitor and the second power source; a second capacitor coupled between a contact of the sixth and seventh switches and a contact of the eighth and ninth switches; and a tenth switch coupled between the second capacitor and the third power source.

In another aspect of the present invention, an apparatus for driving a PDP, the PDP having the panel capacitor, is provided. In the apparatus, first and second switches are coupled in series between a first power source supplying a first voltage and a first terminal of the panel capacitor, and third and fourth switches are coupled in series between the first terminal of the panel capacitor and a second power source supplying a second voltage. A first signal line is coupled to a contact of the first and second switches, and a second signal line is coupled to a contact of the third and fourth switches. A voltage between the first and second signal lines is a third voltage. The first and second voltages are alternately applied to the first terminal of the panel capacitor.

It is preferable that the third voltage is substantially a middle voltage between the first and second voltages.

Preferably, the apparatus further includes a capacitor coupled between the first and second signal lines and charged to the third voltage. A fifth switch may be coupled between a third power source supplying a voltage substantially corresponding to a

summation of the second and third voltages, and be turned on thereby charging the capacitor to the third voltage in the on state of the fourth switch.

The apparatus preferably includes a power recovery section which comprises at least one inductor coupled to the first terminal of the panel capacitor. The power recovery section changes a terminal voltage of the panel capacitor using a resonance generated between the inductor and the panel capacitor.

In still another aspect of the present invention, a method for driving a PDP is provided, the PDP being driven by alternately applying first and second voltages through first and second signal lines coupled to a first terminal of a panel capacitor. The method includes: applying a third voltage between a contact of first and second switches formed on the first signal lines and a contact of third and fourth switches formed on the second signal lines, while the first voltage is applied to the first terminal of the panel capacitor by turning on the first and second switches; and applying the third voltage between the contact of the first and second switches and the contact of the third and fourth switches, while the second voltage is applied to the first terminal of the panel capacitor by turning on the third and fourth switches.

Preferably, a capacitor coupled between the contact of the first and second switches and the contact of the third and fourth switches is charged to the third voltage.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a schematic diagram of a driver circuit according to prior art.

Fig. 2 is a timing diagram showing a driving operation of the driver circuit according to prior art.

Fig. 3 is a schematic diagram of a plasma display panel according to the present invention.

Figs. 4, 7, and 10 are circuit diagrams showing a driver circuit of a plasma display panel according to first to third embodiments of the present invention, respectively.

Figs. 5A and 5B are illustrations showing a current path in each mode of the driver circuit according to the first embodiment of the present invention.

Figs. 6 and 9 are timing diagrams showing a driving operation of the driver circuits according to the first and second embodiments of the present invention, respectively.

Figs. 8A to 8H are illustrations showing a current path in each mode of the driver circuit according to the second embodiment of the present invention.

### **DETAILED DESCRIPTION**

First, reference will be made to Fig. 3 to describe the schematic structure of a PDP according to an embodiment of the present invention.

Fig. 3 is a schematic of the PDP according to the embodiment of the present invention.

The PDP according to the embodiment of the present invention comprises, as shown in Fig. 3, plasma panel 100, address driver 200, scan/sustain driver 300, and controller 400.

Plasma panel 100 comprises a plurality of address electrodes A1 to Am arranged in columns, and a plurality of scan electrodes (hereinafter referred to as "Y electrodes") Y1 to Yn and sustain electrodes (hereinafter referred to as "X electrodes") X1 to Xn alternately arranged in rows. Address driver 200 receives an address drive control signal from controller 400, and applies a display data signal for selection of discharge cells to be displayed to the individual address electrodes. Scan/sustain driver 300 receives a sustain discharge control signal from controller 400, and applies a sustain discharge pulse alternately to the X and Y electrodes. The input sustain discharge pulse applied causes a sustain discharge on the selected discharge cells. Controller 400 receives an external picture signal, generates the address drive control signal and the sustain discharge control signal, and applies them to address driver 200 and scan/sustain driver 300, respectively.

Below is a description of a driver circuit of scan/sustain driver 300 according to a first embodiment of the present invention with reference to Figs. 4 to 6.

Fig. 4 is a circuit diagram of the driver circuit according to the first embodiment of the present invention. Figs. 5A and 5B are illustrations showing a current path in each mode of the driver circuit according to the first embodiment of the present invention, and Fig. 6 is a timing diagram showing a driving operation of the driver circuits according to the first embodiment of the present invention.

The driver circuit according to the first embodiment of the present invention comprises, as shown in Fig. 4, Y electrode driver 310, X electrode driver 320, Y electrode clamping section 330, and X electrode clamping section 340.

Y electrode driver 310 and X electrode driver 320 are coupled to each other with panel capacitor  $C_p$  therebetween. Y electrode driver 310 comprises switches  $Y_s$  and  $Y_h$  coupled in series between power source  $V_1$  and the Y electrodes of panel capacitor  $C_p$ , and switches  $Y_L$  and  $Y_g$  are coupled in series between the Y electrodes of panel capacitor  $C_p$  and power source  $V_2$ .

Likewise, X electrode driver 320 comprises switches  $X_s$  and  $X_h$  coupled in series between power source  $V_1$  and the X electrodes of panel capacitor  $C_p$ , and switches  $X_L$  and  $X_g$  coupled in series between the X electrodes of panel capacitor  $C_p$  and power source  $V_2$ .

Y clamping section 330 comprises switch  $Y_u$  and capacitor  $C_1$ . Switch  $Y_u$  is coupled between a contact of switches  $Y_s$  and  $Y_h$  and ground terminal 0, and capacitor  $C_1$  is coupled between the contact of switches  $Y_s$  and  $Y_h$  and a contact of switches  $Y_L$  and  $Y_g$ . Likewise, X clamping section 340 comprises switch  $X_u$  and capacitor  $C_2$ . Switch  $X_u$  is coupled between a contact of switches  $X_s$  and  $X_h$  and ground terminal 0, and capacitor  $C_2$  is coupled between the contact of switches  $X_s$  and  $X_h$  and a contact of switches  $X_L$  and  $X_g$ .

Although switches  $Y_s$ ,  $Y_h$ ,  $Y_L$ ,  $Y_g$ ,  $Y_u$ ,  $X_s$ ,  $X_h$ ,  $X_L$ ,  $X_g$ , and  $X_u$  included in Y and X electrode drivers 310 and 320 and Y and X clamping sections 330 and 340 are denoted as MOSFETs in Fig. 4, they are not specifically limited to MOSFETs, and may include any switches that perform the same or similar functions. Preferably, the switches have a body diode.

Below is a description of a driving method of the driver circuit according to the first embodiment of the present invention with reference to Figs. 5A, 5B, and 6.

In the first embodiment of the present invention, it is assumed that the voltages supplied by power sources  $V_1$  and  $V_2$  are  $V_s/2$  and  $-V_s/2$ , respectively, and that capacitors  $C_1$  and  $C_2$  are charged to voltage  $V_s/2$ . It is also assumed that voltage  $V_s/2$  is a half of sustain discharge voltage  $V_s$  necessary for a sustain discharge of the panel.

First, as shown in Fig 6, in mode 1 (M1), switches Ys, Yh, Xg, XL, and Xu are turned on, with switches Xs, Xh, Yg, YL, and Yu off.

As shown in Fig 5A, switches Ys and Yh in the on state cause voltage  $V_s/2$  of power source V1 to be applied to the Y electrodes of panel capacitor Cp, and switches XL and Xg in the on state cause voltage  $-V_s/2$  of power source V2 to be applied to the X electrodes of panel capacitor Cp. Y and X electrode voltages Vy and Vx of panel capacitor Cp are  $V_s/2$  and  $-V_s/2$ , respectively, so that the voltage applied to both terminals of panel capacitor Cp is sustain discharge voltage Vs. When switch Xu is turned on, capacitor C2 is charged and clamped to voltage  $V_s/2$  by power source V2 and ground terminal 0.

The voltage of both terminals of switch YL is clamped to voltage  $V_s/2$  stored in capacitor C1 by the switch Yh in the on state. Switches Ys and Yh in the on state cause the voltage difference Vs between power sources V1 and V2 to be applied to switches YL and Yg. The voltage of both terminals of switch Yg is clamped to voltage  $V_s/2$  since the voltage of both terminals of switch YL is clamped to voltage  $V_s/2$ .

Likewise, the voltage of both terminals of switch Xh is clamped to voltage  $V_s/2$  stored in capacitor C2 by switch XL in the on state. Switches XL and Xg in the on state cause the voltage difference Vs between power sources V1 and V2 to be applied to switches Xs and Xh. The voltage of both terminals of switch Xs is clamped to voltage  $V_s/2$  since the voltage of both terminals of switch Xh is clamped to voltage  $V_s/2$ .

Accordingly, the withstand voltages of switches YL, Yg, Xs, and Xh in the off state are clamped to  $V_s/2$  in mode 1.

Next, as shown in Fig 6, in mode 2 (M2), switches Xs, Xh, Yg, YL, and Yu are turned on, with switches Ys, Yh, Xg, XL, and Xu off.

As shown in Fig 5B, switches Yg and YL in the on state cause voltage  $-V_s/2$  of power source V2 to be applied to the Y electrodes of panel capacitor Cp, and switches Xs and Xh in the on state cause voltage  $V_s/2$  of power source V1 to be applied to the X electrodes of panel capacitor Cp. Therefore, Y and X electrode voltages Vy and Vx of panel capacitor Cp are  $-V_s/2$  and  $V_s/2$ , respectively, so that the voltage applied to both terminals of panel capacitor Cp is Vs.

As described in mode 1 (M1), the voltage of both terminals of switch Yh is clamped to voltage  $V_s/2$  stored in capacitor C1 by switch YL in the on state. Since switch Yh is



clamped to voltage  $V_s/2$  and switches  $Y_L$  and  $Y_g$  are in the on state, the voltage of both terminals of switch  $Y_s$  is clamped to  $V_s/2$  by power sources  $V_1$  and  $V_2$ . Likewise, switch  $X_L$  is clamped to voltage  $V_s/2$  stored in capacitor  $C_2$ , and switch  $X_g$  is clamped to voltage  $V_s/2$  by power sources  $V_1$  and  $V_2$ .

Thus, the withstand voltages of switches  $Y_s$ ,  $Y_h$ ,  $X_L$ , and  $X_g$  in the off state are clamped to  $V_s/2$  in mode 2.

According to the first embodiment of the present invention, the voltage applied to switches  $Y_s$ ,  $Y_h$ ,  $X_L$ , and  $X_g$  and switches  $Y_L$ ,  $Y_g$ ,  $X_s$ , and  $X_h$  is clamped to  $V_s/2$  by capacitors  $C_1$  and  $C_2$ , respectively, while the voltage of both terminals of panel capacitor  $C_p$  is maintained to voltage  $V_s$ . Furthermore, a high inrush current hardly occurs in the initial starting step, because capacitors  $C_1$  and  $C_2$  are not used for applying a negative voltage to the Y or X electrodes of panel capacitor  $C_p$ .

Because of the capacitance component of panel capacitor  $C_p$ , a reactive power as well as the power for a discharge is required in applying a waveform for a sustain discharge. A circuit for recovering the reactive power and reusing it is called "power recovery circuit". Below is a description of another embodiment having a power recovery circuit added to the driver circuit according to the first embodiment of the present invention with reference to Figs. 7 to 9.

Fig. 7 is a circuit diagram of a driver circuit according to a second embodiment of the present invention.

The driver circuit according to the second embodiment of the present invention further comprises, as shown in Fig. 7, Y and X electrode power recovery sections 350 and 360 added to the driver circuit according to the first embodiment of the present invention.

Y electrode power recovery section 350 comprises inductor  $L_1$  and switches  $Y_r$  and  $Y_f$ . Inductor  $L_1$  is coupled to a contact of switches  $Y_h$  and  $Y_L$ , i.e., the Y electrodes of panel capacitor  $C_p$ , and switches  $Y_r$  and  $Y_f$  are coupled in parallel between inductor  $L_1$  and ground terminal 0. Y electrode power recovery section 350 further comprises diodes  $D_1$  and  $D_2$  coupled between switch  $Y_r$  and inductor  $L_1$  and between switch  $Y_f$  and inductor  $L_1$ , respectively. Diodes  $D_1$  and  $D_2$  interrupt current paths that may be formed by body diodes of switches  $Y_r$  and  $Y_f$ , respectively.

X electrode power recovery section 360 comprises inductor L2 and switches Xr and Xf, and additionally includes diodes D3 and D4. X electrode power recovery section 360 is the same in construction as Y electrode power recovery section 350 and will not be described in detail. Switches Yr, Yf, Xr, and Xf of Y and X electrode power recovery sections 350 and 360 may comprise MOSFETs.

Below is a description of a driving method of the driver circuit according to the second embodiment of the present invention with reference to Figs. 8A to 8H and 9.

Figs. 8A to 8H are illustrations showing a current path in each mode of the driver circuit according to the second embodiment of the present invention, and Fig. 9 is a timing diagram showing a driving operation of the driver circuits according to the second embodiment of the present invention.

In the second embodiment of the present invention, it is assumed that before the start of the mode 1 (M1), switches Ys, Yh, Xg, XL, and Xu are in the on state, with switches Xs, Xh, Yg, YL, Yu, Xr, Yf, Xf, and Yr off. It is also assumed that capacitors C1 and C2 are charged to voltage  $V_s/2$  and that the inductance of inductors L1 and L2 is L.

Reference will be made to Fig. 8A and 9 to describe the operation in mode 1 (M1).

Before the start of mode 1, current path 81 is formed that includes power source V1, switches Ys and Yh, panel capacitor Cp, switches XL and Xg, and power source V2. Then Y electrode voltage Vy of panel capacitor Cp is sustained at  $V_s/2$  due to power source V1, and X electrode voltage Vx of panel capacitor Cp is sustained at  $-V_s/2$  due to power source V2. Capacitor C2 is clamped to  $V_s/2$  due to current path 82 which includes ground terminal 0, switch Xu, the capacitor C2, switch Xg, and power source V2. The withstand voltages of the switches YL and Yg are clamped to  $V_s/2$  due to the voltage  $V_s/2$  stored in capacitor C1, and the withstand voltages of the switches Xs and Xh are clamped to  $V_s/2$  due to the voltage  $V_s/2$  stored in capacitor C2, as described in the first embodiment.

When switches Yf and Xr are turned on, formed are current path 83 which includes power source V1, switch Ys and Yh, inductor L1, diode D2, switch Yf, and ground terminal 0, and current path 84 that includes ground terminal 0, switch Xr, diode D3, inductor L2, switches XL and Xg, and power source V2. The magnitude of currents IL1 and IL2 flowing

to the inductors L1 and L2 is linearly increased with a slope of  $V_s/2L$  through current paths 82 and 83. Due to currents  $IL1$  and  $IL2$ , energy is stored in inductors L1 and L2.

Reference will be made to Fig. 8B and 9 to describe the operation in mode 2 (M2).

In mode 2 (M2), with switches Yf and Xr on, switches Ys, Yh, Xg, XL, and Xu are turned off. Then, current path 85 is formed that includes switch Xr, diode D3, inductor L2, panel capacitor Cp, inductor L1, diode D2, and switch Yf, so that an LC resonance current flows due to inductors L1 and L2 and panel capacitor Cp. With this LC resonance current, Y electrode voltage Vy of panel capacitor Cp is reduced to  $-V_s/2$  and X electrode voltage Vx is increased to  $V_s/2$ . Y electrode voltage Vy does not exceed  $-V_s/2$  due to the body diodes of switches YL and Yg, and X electrode voltage Vx does not exceed  $V_s/2$  due to the body diodes of switches Xs and Xh.

As described above, energy is previously stored in inductors L1 and L2, and the stored energy and the LC resonance current are used for changing Y and X electrode voltages Vy and Vx of panel capacitor Cp. Thus Y and X electrode voltages Vy and Vx can be changed to  $V_s/2$  and  $-V_s/2$ , respectively, even in the actual circuit including parasitic components.

Reference will be made to Fig. 8C and 9 to describe the operation in mode 3 (M3).

In mode 3 (M3), when Y and X electrode voltages Vy and Vx of the panel capacitor Cp are  $-V_s/2$  and  $V_s/2$ , respectively, the switches Xs, Xh, Yg, and YL are turned on. Then path 86 is formed that includes power source V1, switches Xs and Xh, panel capacitor Cp, switches YL and Yg, and power source V2, and Y and X electrode voltages Vy and Vx of panel capacitor Cp are sustained at  $V_s/2$  and  $-V_s/2$ , respectively.

Current  $IL1$  flowing to inductor L1 is recovered to ground terminal 0 through path 87 which includes the body diodes of switches Yg and YL, inductor L1, diode D2, and switch Yf. Current  $IL2$  flowing to inductor L2 is recovered to power source V1 through path 88 which includes switch Xr, diode D3, inductor L2, and the body diodes of switches Xh and Xs. Therefore, the magnitude of currents  $IL1$  and  $IL2$  is linearly reduced to 0A with a slope of  $V_s/2L$ .

When switch Yu is turned on, capacitor C1 is charged and clamped to voltage  $V_s/2$  through loop 89 which includes ground terminal 0, switch Yu, capacitor C1, switch Yg, and power source V2. As described in the first embodiment, the withstand voltages of switches

$V_s$  and  $V_h$  are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor  $C_1$ , respectively, and the withstand voltages of switches  $X_L$  and  $X_g$  are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor  $C_2$ , respectively.

Reference will be made to Fig. 8D and 9 to describe the operation in mode 4 (M4).

In mode 4 (M4), when currents  $I_{L1}$  and  $I_{L2}$  are 0A, switches  $Y_f$  and  $X_r$  are turned off so that paths 87 and 88 are interrupted. Y and X electrode voltages  $V_y$  and  $V_x$  are still sustained at  $-V_s/2$  and  $V_s/2$ , respectively, due to switches  $Y_L$ ,  $Y_g$ ,  $X_s$ , and  $X_h$  which are turned on. In addition, the withstand voltages of switches  $Y_s$ ,  $Y_h$ ,  $X_L$ , and  $X_g$  are clamped to  $V_s/2$  as described in mode 3 (M3).

Reference will be made to Figs. 8E and 9 to describe the operation in mode 5 (M5).

In mode 5 (M5), energy is stored in inductors  $L_1$  and  $L_2$  while Y and X electrode voltages  $V_y$  and  $V_x$  of panel capacitor  $C_p$  are sustained at  $-V_s/2$  and  $V_s/2$ . In detail, when switches  $Y_r$  and  $X_f$  are turned on, current path 90 is formed that includes ground terminal 0, switch  $Y_r$ , diode  $D_1$ , inductor  $L_1$ , switches  $Y_L$  and  $Y_g$ , and power source  $V_2$ , and current path 91 is formed that includes power source  $V_1$ , switches  $X_s$  and  $X_h$ , inductor  $L_2$ , diode  $D_4$ , switch  $X_f$ , and ground terminal 0. By current paths 90 and 91, currents  $I_{L1}$  and  $I_{L2}$  flowing to inductors  $L_1$  and  $L_2$  are linearly increased with a slope of  $V_s/2L$ . The energy is stored in inductors  $L_1$  and  $L_2$  due to currents  $I_{L1}$  and  $I_{L2}$ .

Reference will be made to Figs. 8F and 9 to describe the operation in mode 6 (M6).

In mode 6 (M6), with the switches  $Y_f$  and  $X_r$  on, switches  $X_s$ ,  $X_h$ ,  $Y_g$ ,  $Y_L$ , and  $X_u$  are turned off after the energy is stored in inductors  $L_1$  and  $L_2$ . Then path 92 is formed that includes switch  $Y_r$ , diode  $D_1$ , inductor  $L_1$ , panel capacitor  $C_p$ , inductor  $L_2$ , diode  $D_4$ , and switch  $X_f$ . Path 92 makes an LC resonance current flow due to the inductors  $L_1$  and  $L_2$  and the panel capacitor  $C_p$ . With this LC resonance current, Y electrode voltage  $V_y$  of panel capacitor  $C_p$  is increased to  $V_s/2$  and X electrode voltage  $V_x$  is decreased to  $-V_s/2$ . Y electrode voltage  $V_y$  does not exceed  $V_s/2$  due to the body diode of switches  $Y_s$  and  $Y_h$ , and X electrode voltage  $V_x$  does not exceed  $-V_s/2$  due to the body diode of switches  $X_L$  and  $X_g$ .

As described in mode 2 (M2), in mode (M6), after the energy is stored in inductors  $L_1$  and  $L_2$ , Y and X electrode voltages  $V_y$  and  $V_x$  are changed by using this energy and the LC resonance current. Therefore Y and X electrode voltages  $V_y$  and  $V_x$  can be

changed to  $V_s/2$  and  $-V_s/2$ , respectively, even in the actual circuit including parasitic components.

Reference will be made to Figs. 8G and 9 to describe the operation in mode 7 (M7).

In mode 7 (M7), when Y and X electrode voltages  $V_y$  and  $V_x$  are  $V_s/2$  and  $-V_s/2$ , switches  $Y_s$ ,  $Y_h$ ,  $X_g$ , and  $X_L$  are turned on to sustain these voltages  $V_y$  and  $V_x$ . Then, path 81 is formed that includes power source  $V_1$ , switches  $Y_s$  and  $Y_h$ , panel capacitor  $C_p$ , switches  $X_L$  and  $X_g$ , and power source  $V_2$  so that Y and X electrode voltages  $V_y$  and  $V_x$  of panel capacitor  $C_p$  are sustained at  $V_s/2$  and  $-V_s/2$ , respectively.

Current  $IL_1$  flowing to inductor  $L_1$  is recovered to power source  $V_1$  through path 93 that includes switch  $Y_r$ , diode  $D_1$ , inductor  $L_1$ , and the body diodes of switches  $Y_h$  and  $Y_s$ . Current  $IL_2$  flowing to inductor  $L_2$  is recovered to ground terminal 0 through current path 94 that includes the body diodes of switches  $X_g$  and  $X_L$ , inductor  $L_2$ , diode  $D_4$ , and switch  $X_f$ .

In addition, when switch  $X_u$  is turned on, capacitor  $C_2$  is charged and clamped to  $V_s/2$  through path 82 which includes switch  $X_u$ , capacitor  $C_2$ , switch  $X_g$ , and power source  $V_2$ . As described above in regard to mode 1 (M1), the withstand voltages of switches  $Y_L$  and  $Y_g$ , are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor  $C_1$ , and the withstand voltages of switches  $X_s$  and  $X_h$  are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor  $C_2$ .

Reference will be made to Figs. 8H and 9 to describe the operation in mode 8 (M8).

In mode 8 (M8), switches  $Y_r$  and  $X_f$  are turned off so that paths 93 and 94 are interrupted, when currents  $IL_1$  and  $IL_2$  flowing to inductors  $L_1$  and  $L_2$ . Switches  $Y_s$ ,  $Y_h$ ,  $X_L$ , and  $X_g$  in the on state cause Y and X electrode voltages  $V_y$  and  $V_x$  of panel capacitor  $C_p$  to be still sustained at  $V_s/2$  and  $-V_s/2$ , respectively. As described in mode 7 (M7), the withstand voltages of switches  $X_s$ ,  $X_h$ ,  $Y_L$ , and  $Y_g$  are clamped to  $V_s/2$ .

Subsequently, the cycle of modes 1 to 8 (M1-M8) is repeated to generate Y and X electrode voltages  $V_y$  and  $V_x$  swinging between  $V_s/2$  and  $-V_s/2$ , thereby sustaining the potential difference between the X and Y electrodes at sustain discharge voltage of  $V_s$ .

Although each of Y and X electrode power recovery sections 350 and 360 has one inductor in the second embodiment of the present invention, all other differently modified power recovery sections may be used. For example, Y electrode power recovery section

350 may include inductors L11 and L12 each forming a different path. More specifically, energy is stored in the inductor L11 while Y electrode voltage  $V_y$  is sustained at  $V_s/2$ , and then used to change Y electrode voltage  $V_y$  to  $-V_s/2$ . Then, the energy stored in inductor L11 is recovered and energy is stored in inductor L12, while Y electrode voltage  $V_y$  is sustained at  $-V_s/2$ . The energy stored in inductor L12 is used to change Y electrode voltage  $V_y$  to  $V_s/2$ .

Although the voltages supplied by power sources V1 and V2 are  $V_s/2$  and  $-V_s/2$ , respectively, in the first and second embodiments of the present invention, a different voltage can also be used as long as the voltage difference between two power sources V1 and V2 is  $V_s$  which is necessary for sustain discharge. Namely, the voltages supplied by power sources V1 and V2 can be  $V_h$  and  $(V_h - V_s)$  so that Y and X electrode voltages  $V_y$  and  $V_x$  swing between  $V_h$  and  $(V_h - V_s)$ .

An exemplary third embodiment in which the voltages supplied by power sources V1 and V2 of Fig. 4 are sustain discharge voltage  $V_s$  and ground voltage 0V, respectively, will be described with reference to Fig. 10.

Fig. 10 is a circuit diagram showing a driver circuit of a plasma display panel according to the third embodiment of the present invention.

As shown in Fig. 10, in the driving circuit according to the third embodiment, power sources V3 and V4 supply the voltages  $V_s/2$ , respectively. In detail, power sources V3 and V4 are coupled in series and supply voltage  $V_s$ . Switches Ys and Xs are coupled to power sources V3, and switches Yg and Xg are coupled to ground terminal 0. Switches Yu and Xu are a contact of power sources V3 and V4.

Except for the voltages applied to the Y and X electrode of panel capacitor  $C_p$ , the operation of the driver circuit according to the third embodiment of the present invention is the same to that of the first embodiment. In addition, capacitor C1 is charged to  $V_s/2$  when switch Yu is turned on, and capacitor C2 is charged to  $V_s/2$  when switch Xu is turned on.

In detail, in mode 1, voltages  $V_s$  and 0V are applied to the Y and X electrode of panel capacitor  $C_p$ , respectively. The withstand voltage of switch YL is clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor C1. The withstand voltage of switch Yg is clamped to  $V_s/2$  due to the voltage of both terminals  $V_s/2$  of switch Yg and voltage  $V_s$  supplied by serially coupled power sources V3 and V4. Likewise, the withstand voltage of switch Xh is

clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor C2. The withstand voltage of switch  $X_s$  is clamped to  $V_s/2$  due to the voltage of both terminals  $V_s/2$  of switch  $X_h$  and voltage  $V_s$  supplied by power sources  $V_3$  and  $V_4$ .

In mode 2, voltages 0V and  $V_s$  are applied to the Y and X electrode of panel capacitor  $C_p$ , respectively. As described above, the withstand voltages of switches  $Y_s$  and  $Y_h$  are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor C1 and voltage  $V_s$  supplied by power sources  $V_3$  and  $V_4$ . Likewise, the withstand voltages of switches  $X_L$  and  $X_g$  are clamped to  $V_s/2$  due to voltage  $V_s/2$  stored in capacitor C2 and voltage  $V_s$  supplied by power sources  $V_3$  and  $V_4$ .

In addition, although the two switches are coupled between the power source and the X or Y electrode of panel capacitor  $C_p$  in the first to third embodiments of the present invention, the number of switches is not specifically limited in the present invention. For example, when four switches  $S_1$ ,  $S_2$ ,  $S_3$ , and  $S_4$  are coupled in series between power source  $V_1$  and the Y electrode of panel capacitor  $C_p$  and switch  $Y_u$  is coupled to the contact of switches  $S_2$  and  $S_3$  in Fig. 4, the withstand voltage of the switches  $S_1$  and  $S_2$  or the switches  $S_3$  and  $S_4$  is  $V_s/2$ .

According to the present invention, the withstand voltage of the switches can be half of voltage  $V_s$  necessary for sustain discharge, thereby reducing the production unit cost. The present invention also eliminates an inrush current generated when the voltage stored in an external capacitor is used in changing the terminal voltage of the panel capacitor. Furthermore, the driver circuit of the present invention can be used irrespective of the waveform of sustain pulses by changing the power source applied to it.

While this invention has been described in connection with what is presently considered to be practical embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.